

### Special Features include:

Designed for use in CCTV applications

High Resolution: 1280 x 1024 (SXGA)

Horizontal Resolution 600 TV Lines

Multiple inputs: 2 Composite BNC, VGA, S-Video

2 BNC Looping Outputs

Brightness of 300 cd/m,

Contrast of 700:1

Advanced Image Scaling

3-D Comb Filter

2 Audio Inputs and 2 Audio Looping Outputs

19" Rack Mountable

VESA Wall-Mount Compatible (100mm x 100mm)

Built-in Power Adapter

### 19" TFT LCD Monitor



Back



Side

**System**

Panel Size	19" LCD TFT (Thin-Film Transistor)
Resolution	1280 x 1024 (SXGA)
Horizontal Resolution	600 TV Lines
Contrast Rate	700:1
Brightness	300 cd/m <sup>2</sup>
Aspect Ratio	5:4
View Angle	H : 135, V :150
Response Time	8 ms
Video Signal	Composite signal 0.5~2 Vp-p/75 Ω , Y:1 Vp-p, C:0.3 Vp-p
Video Mode	NTSC/PAL Auto Scanning
Scan Frequency	H:30K~60KHz, V:56~75Hz
3D Comb Filter	Yes
Regulatory Approvals	cUL, CE class B, FCC-B

**Operation**

Front Pannel Controls	Menu, Up, Down, Volumne up/down, Tint, Color, Bright, Contrast
Indicators	Power On LED, Video Source (V1, V2, S-Video, PC/DVI)
OSD Control	Color Temp, Utility, OSD, Language (6)
OSD Language	English, Francais, Deutsch, Espanol, Danish, Italiano

**Connector**

Input	D-Sub x 1 (0.7 Vp-p), DVI (option) Video Input (BNC) x 2 Video Input (S-Video) x 1 Audio Input (RCA) x 2
Output	Video Looping Out (BNC) x 2 Audio Looping Out (RCA) x 2

**Mechanical & Electric Design**

Glass Frame	Yes
Audio Speaker	0.5W x 1
Looping 75	Yes
VESA Spec.	100mm x 100mm
Frame Material	Steel
Back Material	Steel
Base Material	Steel
Power	AC 100 - 240V, 50/60Hz Auto Switchable
Power Consumption	30 Watts, Standby 5 Watts
Unit Dimension (W x H x D)	15.3 x 14.5 x 2.5 inches (390 x 366 x 65mm)
Color	Black

**Accessory**

Power Cord	1 set
15 pin D-Sub Cable	1 set

\*Design and specifications are subject to change without notice

**Lekson Video**

3214 North University Ave. #528, Provo, UT 84604

Tel: 1-888-LEKSON1 | Fax: (801) 227-7819

[www.leksonvideo.com](http://www.leksonvideo.com)