

### Special Features include:

Superior Color Reproduction  
and Picture Clarity

Resolution: 450 TV Lines

Automatic Switching System  
(NTSC/PAL)

Digital Comb Filter for  
Significantly Improved Picture  
Quality

Front Panel Controls

Built-in Speaker

2 Video Inputs Looping

2 Audio Inputs Looping

S-VHS Input for Seperate Y-C  
Signals

Free Voltage Input (100-240  
VAC)

Optional Rack Mount  
Available

### 21" Color CCTV Monitor



### System

Display Tube	21" Line gun, Semi tinted CPT 90° deflection angle
Horizontal Resolution	450 TV Lines
Video Input	2 BNC, 1 S-VHS (Y/C)
Video Output	2 BNC
Audio Input	2 RCA
Audio Output	2 RCA
Sync Format	NTSC / PAL
Linearity	Horizontal: 10%; Vertical: 10%
Controls (Front Panel)	Volume, Brightness, Contrast, Color, Tint, Video Input V1/V2/S-Video selector switch, Power (On./Off switch)
Connectors	Video 1: Composite Video - 2 BNC (1 in, 1 out) Video 2: Composite Video - 2 BNC (1 in, 1 out) Y/C In Audio 1: 2 RCA phono jacks (1 in, 1 out) Audio 2: 2 RCA phono jacks (1 in, 1 out) Power Cord: 1 detachable 3-wire IEC connectors with grounded plug

### Mechanical and Electrical

Rated Voltage	100-240 VAC, 50/60 Hz
Voltage Range	90 to 264
Power at Rated Voltage	67 W
Dimensions	18.74(W) x 16.93(H) x 18.43(D) inches (476 x 430x 468 mm)
Net Weight	52.8 lbs (24 Kg)
Cabinet	Material: Steel with plastic front

### Environmental

Operating Temperature	32° - 104° F (0° - 40° C)
Operating Humidity	35% - 80% RH (non-condensing)

### Product Regulatory Compliance

Product Regulatory Compatibility	Complies with FCC part 15, ICES-003 and CE regulations
Product Safety	Complies with CE regulations, cULus

\*Design and specifications are subject to change without notice

## Additional Lekson Products



Digital Video Recorders



CCTV LCD Monitors



Public View Monitors



IR Security Cameras

## Lekson Video

3214 North University Ave. #528, Provo, UT 84604

Tel: 1-888-LEKSON1 | Fax: (801) 227-7819

[www.leksonvideo.com](http://www.leksonvideo.com)