

Special Features include:

High Resolution : 1280 x1024 (XGA)

Brightness of 250 cd/□

Contrast of 400:1

19" Rack Mountable

VESA Wall-Mount Compatible
(100□ x 100□)

15" LCD Monitor



Side

Panel

Type	15"
Pixel Pitch	0.297mm (H) x 0.297mm (W)
Viewing Angle (CR ≥ 5)	Horizontal : 120° (Left/Right) Vertical : 140°
Display Area	304.1mm (H) x 228.1mm (V)
Display Colors	16.2 Million Color
Number of dots	(1024 x 768), RGB Stripe
Contrast Ratio	400:1 (Typical), Normally White
Brightness	250 cd/□ (Typical)
Response Time	25ms (Rising + Falling)
Scanning Frequency	Horizontal : 31 ~ 82KHz Vertical : 56 ~ 78Hz
Lamp life Time	50,000Hrs (Typical)
Recommended Resolution	1024 x 768 / 60Hz
Surface Treatment	Anti-Glare and Hard-Coating (3H)

In/Out

PC	RGB Analog 0.7 Vpp (H/V separated Sync. : TTL), D-Sub mini 15 pin
Audio	Stereo Audio in (PC), Stereo Audio out (headphone), Φ3.5
Speaker(built-in)	Option (Stereo output : 2W Max. x 2CH.)
Video	Option (Composite x 1ea & S-Video x 1ea)
DVI	Option

Function

Scaling	Up/Down Scaling
Tilt Angle	+3° ~ -20° (Front/Rear)
OSD Language	6 Languages (English, Japanese, French, German, Italiano, Spanish)
Stand	Stand Type, Wall Mountable
User Controls	Auto Adjust, Brightness, Contrast, Position, Image, Volume, Color, Language, OSD Adjust, Miscellaneous

Power

Power Supply	AC 110 ~ 240V, 1.5A, 50/60Hz Input
Power Consumption	25 Watts
Power Management	VESA DPMS Compatible
Power Saving	EPA Energy Star

Others

Temperature	Operation : 32° ~ 104°F (0° ~ 40°C) Storage : -4° ~ 140°F (-20° ~ 60°C)
Product Color	Black
Dimensions (WxHxD)	13.85" x 14.5" x 6.7" (352 x 368 x 170mm)
Weight	Net : 9.25 lbs (4.2Kg) Gross : 11.5 lbs (5.2Kg)
Regulations	MIC, UL/cUL, CE, FCC-B, VCCI-B, TCO95, ISO13406-2, EPA Energy Star
Special Features	Kensington Security Lock, Ergonomic Case, Narrow Bezel, Chromaster™

*Design and specifications are subject to change without notice

Lekson Video

3214 North University Ave. #528, Provo, UT 84604

Tel: 1-888-LEKSON1 | Fax: (801) 227-7819

www.leksonvideo.com